

Class 1
Surround by Laminex® | MR MDF
Building Products Information Requirements | Info. Sheet
Version: Surround by Laminex® | MR MDF | **02.24**

Product name	Surround by Laminex® MR MDF
Product line	N/A
Product identifier	Surround by Laminex® MR MDF

Place of manufacture

Aotearoa New Zealand	
Overseas	✓

Product description

Surround by Laminex® MR MDF is designed for interior area applications and is manufactured from Moisture Resistant (MR), Medium Density Fibreboard (MDF).

Each panel has one face routed with a regular decorative pattern which is pre-primed with water-based paint.

The majority of Surround by Laminex® MR MDF panels are 12mm thick. One profile (Classic VJ 100) is 9mm thick.

All 12mm panels have a reverse flat face sealed with a white Low-Pressure Melamine (LPM). 9mm panels has a raw MDF reverse flat face.

Key technical specifications:

Surround by Laminex® MR MDF is available in two sheet sizes (dimensions in mm):

	Weight 12mm	Weight 9mm
• 2400(h) x 1200(w)	9.2kg/m ² - 26.5kg	6.9kg/m ² - 19.9kg
• 3000(h) x 1200(w)	9.2kg/m ² - 33.1kg	6.9kg/m ² - 24.9kg

Surround by Laminex® MR MDF profiles run parallel with the height of the sheet (i.e. with the length of the 2400(h) and 3000(h) direction.

Surround by Laminex[®] MR MDF sheets use a tongue and groove joining system. Surround by Laminex[®] MR MDF has a white polypropylene tongue.

Note: All dimensions and measurements are nominal.

Relevant building code clauses

- B1 Structure - B1.3.1, B1.3.2, B1.3.4, Surround by Laminex[®] MR MDF meets the requirements for loads arising from self-weight and impact [i.e., B1.3.3 (a) and (j)].
- B2 Durability: B2.3.1 (c) 5 years.
- C3 Fire affecting areas beyond the fire source - C3.4 (a)
- F2 Hazardous building materials - F2.3.1

Contributions to compliance

Surround by Laminex[®] MR MDF panel properties are tested in accordance with AS/NZS 4266.1:2017, AS/NZS 1580.408.2 & AS/NZS 1859.2

Scope of use

Surround by Laminex[®] MR MDF panels must be installed in accordance with the Surround by Laminex[®] Fabrication and Installation Manual. This manual has been developed to allow designers, fabricators, installers and DIYers who work with Surround by Laminex to achieve performance standards for both domestic and commercial applications. Laminex[®] New Zealand recommend the Fabrication and Installation Manual is read and understood prior commencing installation. This publication can be downloaded at [Laminex.co.nz](https://laminex.co.nz)

Surround by Laminex[®] MR MDF panels can be fixed directly to timber or steel framing, and to various substrates, including plasterboard, using a combination of adhesive and mechanical fasteners.

Surround by Laminex[®] MR MDF panels have a regular decorative pattern pre-primed face. Panels can be finished with a light sanding, and a minimum of two topcoats of a compatible paint in line with paint manufacturer's guidelines.

Surround by Laminex[®] MR MDF panels have a Fire Material Group Number of 3.

Conditions of use

Surround by Laminex® MR MDF is intended for use as an interior wall and ceiling lining panel for non-structural applications and is not intended for use in exposed exterior locations.

Surround by Laminex® MR MDF panels can be installed in internal moisture areas, provided instructions in section 6.9 of the Fabrication and Installation Manual are strictly followed and adhered to.

Surround by Laminex® MR MDF panels can be curved, provided instructions in section 6.14 of the Fabrication and Installation Manual are strictly followed and adhered to.

Surround by Laminex® Fire Resistant product (E1 MDF MR) is prohibited for use in internal moisture areas – refer to the Information Sheet for this product.

Surround by Laminex® MR MDF panels must not be subjected to submersion or continuous permanent contact with water. Do not use in saunas or steam rooms.

Surround by Laminex® MR MDF panels are not intended for use as a wall bracing panel.

Surround by Laminex® MR MDF panels are not suitable for any cabinetry or flooring applications.

Surround by Laminex® MR MDF is not fire rated as part of a fire protected boundary or fire wall.

Supporting documentation

The following additional documentation supports the above statements:

Title (type)	Version	URL
Surround by Laminex® Fabrication and Installation Manual	Edition 6.0 02.24	Click here
Surround by Laminex® Brochure	02.24	Click here
Surround by Laminex® Design and Specification Guide	02.24	Click here
Surround by Laminex® Warranty	Edition 4.0 02.24	Click here
Surround by Laminex® Fire Certificate	FAS210127 R1.1	Click here
Surround by Laminex® Green Tag	6 April 2023	Click here
Surround by Laminex® 9mm primed VOC Emission Test Certificate	23 May 2022	Click here
Surround by Laminex® Surround by Laminex® 12mm primed VOC Emission Test Certificate	23 May 2022	Click here

Surround by Laminex® Surround by Laminex® 12mm / 9mmMR E0 Formaldehyde Emission Test Certificate	V2.4 03.08.2020	Click here
Surround by Laminex® SDS	2.1.1.1 - 16.03.2021	Click here
Surround by Laminex® Technical Data Sheet (TDS) – MR E0 MDF	V5.0 02.24	Click here
Surround by Laminex® Technical Bulletin – Installation of panels on ceilings	V1.0 02.24	Click here
Surround by Laminex® Technical Bulletin – Curving of panels	V1.0 02.24	Click here

Contact details

Manufacture location	Overseas
Legal and trading name of manufacturer	Laminex Group Pty Limited, trading as Laminex – AU or The Laminex Group.
Manufacturer address for service	332 Bay Rd Cheltenham Victoria 3192 Australia
Manufacturer website	www.laminex.com.au
Manufacturer NZBN	N/A
Manufacturer email	supportservices@laminex.com.au
Manufacturer phone number	+61 132136

Importer location	New Zealand
Legal and trading name of Importer	Fletcher Building Products Limited (company number 952008), trading as Laminex® NZ.
Importer address for service	810 Great South Road Penrose Auckland 1061 New Zealand
Importer website	www.laminex.co.nz
Importer NZBN	9429037626969
Importer email	CSC@laminex.co.nz
Importer phone number	0800 303 606

Warnings and bans

Is the building product/building product line subject to warning or ban under section 26 of the Building Act 2004?

No
